
FERCHER GmbH
FERCHER GmbH, St. Thomas 10, 9400 Wolfsberg, Austria
VATIN: ATU70480437
Corporate register number: FN 448037 d
Commercial court: Landesgericht Klagenfurt
phone: +43 676 606 95 40
web: www.fercher.at
e-mail: office@fercher.at

FERCHER Wastewater-Heatexchanger Type **FB-12/W-2-1** - Datasheet




General	
Model-name / Type:	**FB-12/W-2-1**
Material:	**AISI 316L**
External Dimensions	
Length:	**3 510 mm**
Width:	**1 340 mm**
Height:	**1 750 mm**
Weights	
Empty weight:	**1 205 kg**

Wastewater	
Maximum-Flowrate:	**12,0 L/s**
Max. allowed temperature:	**100 °C**
Wastewater-Inlet:	**pipe D=160**
Wastewater-Outlet:	**pipe D=160**
Freshwater	
Maximum-Flowrate:	**16,8 L/s**
Max. allowed pressure:	**6 bar**
Water-Inlet:	**3 inch external thread**
Water-Outlet:	**3 inch external thread**

Cleaning: Wastewater-side of heatexchanger can be cleaned during full operation, just take off panels and clean (for instance with pressure-cleaner and/or brush)

View: Covers removed



Technical changes in the interest of technical progress are reserved. Errors excepted. This document is the unrestricted intellectual property of FERCHER GmbH.


FERCHER GmbH
FERCHER GmbH, St. Thomas 10, 9400 Wolfsberg, Austria
VATIN: ATU70480437
Corporate register number: FN 448037 d
Commercial court: Landesgericht Klagenfurt
phone: +43 676 606 95 40
web: www.fercher.at
e-mail: office@fercher.at

FERCHER Wastewater-Heatexchanger Type **FB-12/W-2-1** - Characteristic curves


Curves are valid for operation with freshwater-IN-flow of 12,0 L/s at 15°C

*For special/individual calculations please contact us at **office@fercher.at**. We gladly help you with choosing the correct heatexchanger and with calculations.*

Performance curves



freshwater-pressuredrop



Technical changes in the interest of technical progress are reserved. Errors excepted. This document is the unrestricted intellectual property of FERCHER GmbH.